



Thank you for Purchasing a **Honey Badger – Locker Bar.**

Installation Instructions

Tools Required:

Drilling Machine
Hole Saw 25mm
Measuring Tape
Drill Bit 3mm
Small Tube Clear Silicone
Masking Tape 25mm or 50mm Wide
Pad Lock 8mm Stem

Step 1:

Place Locker Bar over Hatch Lids that need to be secured. Make sure that Locker Bar is placed far enough forward on Hatch Lid so that the Hatch Lid opening is minimal with Locker Bar in place.

Step 2:

Stick Masking Tape on both sides of Gun Well in the area where drilling is to be done.

Step 3:

Measure from a Hatch Lid line to Locker Bar to get them parallel. Move until straight in line with the measured Hatch Lid.

Step 4:

With End Caps fitted to the Locker Bar and Locker Bar fully extended, hand press End Caps on to Masking Tape to mark Drilling centres.
Make sure Locker Bar is straight and in line before centres from End Caps are transferred to taped Gun Well
Make sure that End Caps are pressed down on Carpet to allow minimum clearance between Hatch Lid and Locker Bar.

Step 5:

With centres transferred on to Masking Tape use a 3mm Drill Bit to centre drill for Hole Saw. Do one side first to ensure 100% straight line fit.

Step 6:

Use 25mm Hole Saw and carefully drill in to 3mm Pilot Hole. Once through, fit End Cap. Re-check the opposite side for alignment.

Step 7:

Repeat the above process Steps 1 to 6.

Step 8:

Keep the End Cap in place and line up the Mounting Holes horizontal or vertical and use the 3mm Drill Bit to drill through the End Cap holes – using the End Cap as a Drill Jig.

Repeat on other end.

Step 9:

Remove Masking Tape.

Use Silicon Sealant to seal off the End Cap to the Gun Well before screwing it down in to position. Clean off excess Silicon.

Trust the Honey Badger Locker Bar to safeguard and secure your Equipment!

© 2013 www.honeybadgermarineproducts.com